



The panel for the MPE and Combi can now be installed on the side.

## Upgraded sauna heaters

The panel for Combi RC 6, 8 and MPE sauna heaters is now mountable directly on the side of the heater. The pre-punched holes enable installation on either the left hand side or the right hand side. The sauna heaters Combi 4 RC, Combi 6 RC, Combi 8 RC, MPE 6, MPE 8, SE 6, SE 8 and SD change from side- or front cover in metal to ditto in Termosafe. Tylo Termosafe gives a contemporary look and acts as thermal shield when the sauna heater is on.

The new sauna heaters will replace the old ones, as they are gradually phased out.



The new colour on SE sauna heater gives a new impression.



**MPE 6** (Art. no. 6320 2009)

With an easily accessible electronic control panel that may be installed on the side of the sauna heater, inside the sauna room (max. 1 metre above floor level) or outside the sauna room. The panels show time and temperature with light diodes on a scale of 1–10. Max. 3 hours running time. 0–10 hour preset. 6.6 kW output for sauna rooms 4–8 cu.m. Delivered inclusive of 2,5 m cable and mounting bracket for optional installation.

**MPE 8** (Art. no. 6320 3009)

As above, but with 8 kW output for sauna rooms 6–12 cu.m.



**SE 6** (Art. 6020 2019)

Requires separate electronic control panel type CC. 6.6 kW output for sauna rooms 4–8 cu.m.

**SE 8** (Art. 6020 3019)

As above, but with 8 kW output for sauna rooms 6–12 cu.m.



**SDK 10** (Art. 6420 1009)

Requires separate control panel type TS 16, TS 30 or CC with relay box RB 30. 10.7 kW output. For sauna rooms 10–18 cu.m.

**SD 16**

400 V 3-phase (Art. 6420 3000)

230 V 3-phase (Art. 6420 3001)

Requires separate control panel type TS 30 or CC with relay box RB 30. 16 kW output for sauna rooms 15–35 cu.m.

**SD 20**

400 V 3-phase (Art. 6420 4000)

230 V 3-phase (Art. 6420 4001)

As above, but with 20 kW output. Use together with a separate CC control panel with relay box RB 60. For sauna rooms 22–43 cu.m.



**Combi 4 RC** (Art. 6210 5000)

With separate electronic control panel which can be installed on a wall inside the sauna room (max. 1 m above floor level) or at any height outside the sauna room. 4.5 kW output. 400 V (two-phase and neutral). For sauna rooms 1.2–4.5 cu.m. Delivered inclusive of 2,5 m cable.



**Combi 6 RC** (Art. 6210 5049)

With separate electronic control panel which can be installed on the side of the sauna heater, a wall inside the sauna room (max. 1 m above floor level) or at any height outside the sauna room. 6.6 kW output. For sauna rooms 4–8 cu.m. Delivered inclusive of 2,5 m cable and mounting bracket for optional installation of the control panel.



**Combi 8 RC** (Art. 6210 5069)

As Combi 6 RC, but with 8 kW output for sauna rooms 6–12 cu.m.