

**dröm**<sup>®</sup>  
sauna steam spa



A WORLD OF WELLBEING

Dröm UK Ltd. Dröm House, Abbot Close, Byfleet, Surrey, KT14 7JN.

Tel: 01932 355 655 | Fax: 01932 355651

Email: [info@dromuk.com](mailto:info@dromuk.com) | [www.dromuk.com](http://www.dromuk.com)

[WWW.DROMUK.COM](http://WWW.DROMUK.COM)

# Steam bath accessories.



## Steam Guard

### Steam Guard W (Art. 9002 9210)

For wall installation inside the steam room to protect bathers from the hot jet of steam. Recommended in all public facilities.

### Steam Guard 778 (Art. 9002 9220)

As above, but for 778 mm section in Tylö Elysée steam rooms.

### Steam Guard 588 (Art. 9002 9230)

As above, for 588 mm section.

### Steam Guard Corner

(Art. 9002 9240)

As above, for corner section.



## Optical fibre lighting

Halogen lighting for atmospheric lighting in all sorts of settings. The lighting source is in a projector placed outside the sauna room. The length of the optical fibres determines the maximum distance between the projector and the light points.

### Fiber Light Standard

(Art. 9001 1100)

42 W with 6 light points (2 x 2 m, 2 x 2.5 m and 2 x 3 m).

### Fiber Light Public (Art. 9001 1120)

42 W with gilded fittings and 8 light points (2 x 2.5 m, 3 x 3 m and 3 x 3.5 m).

### Fiber Light Colour S (Art. 9001 1125)

75 W with 9 light points (1 x 0.5 m, 2 x 1 m, 3 x 1.6 m, 2 x 1.9 m, 1 x 2.3 m) and a rotating disc for fixed or changing colours.

### Fiber Light Colour (Art. 9001 1130)

75 W, as above but with 9 light points on 2.5 metre cables for large rooms.



### Downlight (Art. 9001 1081)

Effective spotlighting for installation in the steam room. 12 V/5 W. Connect to our 12 V transformer below.

### Transformator 12 V/210 W

(Art. 9090 1015)

200–240 V~/12 V max. 210 W.

### Transformator 12 V/60 W

(Art. 9090 1020)

As above, but for max. 60 W.



## Lighting strips

May be cut to size and installed under the benches in Excellent steam rooms. 12 V. Connect to our 12 V transformer.

### Lighting strip 38 (Art. 9001 1040)

Length 38 cm. 12 W.

### Lighting strip 50 (Art. 9001 1050)

Length 50 cm. 15 W.

### Lighting strip 90 (Art. 9001 1060)

Length 90 cm. 27 W.

### Lighting strip 190 (Art. 9001 1070)

Length 190 cm. 57 W.



## Service section, complete

(Art. 4990 5085)

Wall section in white, vacuum-formed, special-grade plastic. Jet nozzles for water massage, thermostatically controlled mixer tap, shower head, riser rail and soap/shampoo compartments. May be used to replace a wall/seat section.

## Service section (Art. 4990 5081)

As above, but without jet nozzles.



## Fragrance dispensers

### Tylö Fresh (Art. 9090 8005)

Fragrance dispenser for saunas, steam baths and wherever else Tylö's aromatic essences may be needed. Silent, automatic operation. Installation distance: max. 2 metres between fragrance dispenser and nozzle. Up to four fragrance dispensers may be connected to a single control panel for varying the fragrance in one or more rooms. Size: 350 x 200 mm.

### CC Fresh (Art. 9090 8006)

Electronic control panel for easy, automatic operation of Tylö Fresh dispenser. Supplied complete with transformer. May be installed at any distance from the fragrance dispenser. Size: 130 x 190 mm, depth 27 mm.

### Tylö Fresh Basic (Art. 9090 8007)

As Tylö Fresh above, but with transformer and simple on/off function for manual control of the fragrance intensity. May also be connected to lighting, etc. For domestic saunas only.



## Steam jet

### Steam Outlet (Art. 9002 9205)

Steam head with integral dispenser for Tylö fragrances. Connect to the steam generator's steam pipe.

## Descaling agent

### Sulfamic solvent (Art. 9090 3010)

An extra effective descaling agent for professional use only in public facilities. Sold in a 5-kilo pack.

### Solvent 50 (Art. 9090 3007)

Powder for descaling the water tank in Tylö steam generators. Totally odourless and harmless. Sold in packs of 50.



### Loudspeaker A (Art. 9080 2000)

Steam and heat-resistant materials suitable for recessed installation inside the steam room. 50 W output. Installation size: 120 mm diameter, depth 55 mm.

### Loudspeaker B (Art. 9080 3000)

As above, 50 W, but for surface-mounting. Size: 77 x 114 mm, depth 125 mm.

## Disinfecting equipment



### Steam Clean (Art. 9090 8020)

For automatic day-to-day hygiene and disinfection of steam rooms in hotels and public facilities, etc. One hour after completion of the bathing cycle the entire room is automatically flushed with water. A ceiling-mounted sprinkler sprays disinfectant throughout the room and then repeatedly rinses it off with clean water. A security code function ensures that the disinfecting cycle can not be activated accidentally. Steam Clean is indispensable in all public facilities.



### Disinfectant (Art. 9002 9100)

Disinfecting liquid for use with Steam Clean (above). Supplied in a 5-litre plastic container.